

## TECHNICAL SPECIFICATION

	1016900 UK	1016950 FR	1022900 UK	1138700 GmbH	1139600 USA	Units of Measure
Height :	570	570	570	570	570	mm
Width :	325	325	325	325	325	mm
Depth :	345	345	345	345	345	mm
Weight :	25	25	27	25	25	Kg
Airflow :	6.5	6.5	6.5	6.5	6.5	m <sup>3</sup> /min
Voltage :	230	230	110/2	230	115	V
Phase :	1	1	1	1	1	
Frequency :	50	50	50	50	60	Hz
Maximum Power :	0.46	0.46	0.46	0.46	0.46	kW
Maximum Current :	2	2	4 / 2	2	4	A
Generator Size :	1	1	1	1	1	kva
Fuse Rating :	5	5	5 / 13	5	13	A
Effective Volume :	85	85	85	85	85	m <sup>3</sup>
Refrigerant Type :	R134a	R134a	R134a	R134a	R134a	
Refrigerant Quantity :	0.170	0.170	0.170	0.170	0.170	Kg
Normal Extraction :	4.5	4.5	4.5	4.5	4.5	l/24hrs
Maximum Extraction :	20	20	20	20	20	l/24hrs
Noise Level :	Less than 70dba when running					
Finish :	Epoxy Coated Zintec Steel					
Mobility :	Light in construction and easily positioned					
Normal :	Rated Extraction at 15°C 65% RH Conditions					
Maximum :	Rated Extraction at 45°C 99% RH Conditions					

**This machine has been manufactured in the United Kingdom**